

The American University in Cairo
Computer Science & Engineering Department
CSCE 106 "Fundamentals of Computer Science"

Instructor:	Final Exam	Fall 2011
Last Name :		ID:
First Name: Section No.:		

EXAMINATION INSTRUCTIONS

- * Do not turn this page until asked to do so.
- * Exam time is **120** minutes.
- * Put the answers on the same question sheet, do not use any additional papers, even for scratch.
- * Write your name, ID, section no. in the indicated places.
- * Read the exam instructions.
- * Read the honesty policy.
- * Sign the following statement.

Academic Integrity Policy

Cheating in Exams is a violation of the honesty policy of AUC. Whispering, talking, looking at someone else's paper, or copying from any source is considered cheating. Any one who does any of these actions or her/his answers indicates that she/he did any of them, will receive a punishment ranging from zero in this exam to failing the course. If repeated, it may lead to dismissal from AUC.

I have read the honesty policy and exam instructions and I am presenting this exam as entirely my effort.

Signature: _____

DO NOT USE THIS SECTION

Question	Points	Grade
1	15	
2	25	
3	10	
4	15	
5	15	
6	20	
Total	100	

Question 1 (15 points)

Tick only one possible answer for each of the following:

1) $!((x == x) \ \&\& \ (y > 10))$ is equivalent to:

- a. True []
- b. $(x != x) \ \&\& \ (y < 10)$ []
- c. $(x != x) \ || \ (y <= 10)$ []
- d. None of the above []

2) Intellectual Property:

- a. A form of protection that can be granted by the government for an invention; gives exclusive rights of an invention to its inventor for 20 years. []
- b. Standards of moral conduct as they relate to computer use. []
- c. The rights to which creators of original creative works (such as software, artistic, literary works, inventions, and more) are entitled. []
- d. The legal right to sell, publish, or distribute an original software, artistic or literary work; is held by the creator of a work as soon as it exists in physical form. []

3) The value of $((x - 4) != 4) \ \&\& \ ((x - 4) == 4)$ is:

- a. $(x - 4)$ []
- b. True []
- c. $(x + 4)$ []
- d. none of the above []

4) The **Compiler** is a software that:

- a. translates a high-level language program into machine language []
- b. translates an assembly language program into machine language []
- c. lets users display and view a web document []
- d. None of the above []

5) The value of $((x <= y) \ || \ \text{True})$ is:

- a. $(x > y)$ []
- b. $(x <= y)$ []
- c. False []
- d. none of the above []

6) The ALU is the unit of computer responsible of:

- a. Storing programs and data permanently []
- b. Performing arithmetic and logical operations []
- c. Performing Input/Output operations []
- d. None of the above []

7) In binary: $1111 + 1111 = ?$

- a. 10000 []
- b. 11110 []
- c. 11011 []
- d. 11111 []

8) In C++, the statement: **if (1 != 1) cout << 1; else cout << 0;** will produce:

- b. 1 []
- c. $(1 != 1)$ []
- d. 0 []
- d. none of the above []

9) $(10000000)_2$ is equivalent to:

- a. $(256)_{10}$ []
- b. $(127)_{10}$ []
- c. $(128)_{10}$ []
- d. None of the above []

10) An equivalent expression of $((x <= y) \ || \ \text{False})$ is:

- c. $(x > y)$ []
- d. $(x <= y)$ []
- e. False []
- d. none of the above []

Question 2 (25 points)

Show the output of each of the following program segments:

<pre>void drawL(); int func(int n); void main () { drawL(); cout << setw(3) << "k" << setw(8) << "func(k)" << endl; drawL(); for (int k=0; k <= 6; k += 2) cout << setw(3) << k << setw(8) << func(k) << endl; drawL(); } int func(int n) { int f = 1; for (int m=2; m <= n; m++) f = m * f; return f; } void drawL() { for (int c = 1; c <= 11; c++) cout << '-'; cout << endl; }</pre>	
---	--

<pre>float a = 2, b = 2, c = 1.5, x; int d = 4, e = 5.5, y; x = a * b - c + d / e; y = a * (b - c) + e / d; cout << "x = " << setw(4) << x << " y = " << setw(4) << y << endl;</pre>	
---	--

<pre>int x = 1, y = 1, z; y *= x++; cout << "x = " << setw(2) << x << "y = " << setw(2) << y << endl; x = 6; y = 2; z = --x / y++; y = z-- + x++; cout << "x = " << x << " y = " << y << " z = " << z << endl;</pre>	
--	--

.....

.....

.....

.....

.....

.....

.....

<pre> int B[4]; const int two = 2; int n = 11; int c = 3; int nn = n; do { B[c] = nn % two; nn /= two; c--; } while (nn != 0); cout << "The equivalent value of " << n << " is "; for (int c = 0; c < 4; c++) cout << B[c]; cout << endl; </pre>	
---	--

<pre> int myNum (int); void main() { for (int n = 1; n < 6; n++) { for (int m = 1; m <= n; m++) cout << myNum(n); cout << endl; } } int myNum (int nn) { const int one = 1; const int two = 2; const int three = 3; switch(nn % three) { case 1: return one; break; case 2: return two; break; default: return three; } } </pre>	
---	--

.....

.....

.....

.....

.....

.....

Question 3 (10 points)

Draw the Flowchart of the following program and show its final output:

<pre># include <iostream> # include <iomanip> using namespace std; void main() { int a = 5, b = 7, c = 3, t; if (b > a) { t = a; a = b; b = t; } if (c > b) { t = b; b = c; c = t; } if (b > a) { t = a; a = b; b = t; } cout << "a = " << setw(3) << a << endl; cout << "b = " << setw(3) << b << endl; cout << "c = " << setw(3) << c << endl; }</pre>	FlowChart
Program Output	

Question 4 (15 points)

Write a C++ program that uses **only two nested loops** and **switch structure** to produce the following output:

```
@
@ @
@ @ @
& & & &
& & & & &
& & & & & &
@ @ @ @ @ @ @
@ @ @ @ @ @ @ @
@ @ @ @ @ @ @ @ @
& & & & & & & &
```

Question 5 (15 points)

A Perfect integer is a positive integer number greater than 1 and the sum of its factors (including 1) is equal to the number itself. For example, 6 is the first perfect number because $1 + 2 + 3$ (the factors of 6) = 6) and 28 is the next perfect number because the sum of its factors $1 + 2 + 4 + 7 + 14 = 28$ which is equal to the number itself.

The following C++ modular program takes a positive integer number greater than 1 and less than 1000 and prompts the user whether the entered number is perfect or not. There are some missings (represented by dots) in the given program. Complete these missings such that the program could be compiled and run correctly. The program does not accept any integer number outside the given range (greater than 1 and less than 1000).

The Program

```
# include <iostream>
# include <iomanip>
using namespace std;
bool perfect(int);
void main ()
{   int num;
    do
    { cout << "Enter an integer number between 1 and 1000:" << endl;
      cin >> num;
    } while ( .....);

    If ( ..... )
        cout << "The number" << setw(5) << num << "is Perfect" << endl;
    else
        cout << "The number" << setw(5) << num << "is NOT Perfect" << endl;
}

bool ..... (..... n)
{   int sum = .....;

    for ( int c = 1; ..... )
        If ( n % c == 0 )
            .....;

    return (.....);
}
```

Question 6 (20 points)

Write a **modular** C++ program using functions to generate a table showing the area of a circle for a sequence of radius values (integer values). The program should read the start integer radius (startRad), the end integer radius (endRad) and the step value (stepVal). The program should validate the user input through enforcing the following conditions:

- The start integer radius should be greater than 0 and less than 100.
- The difference between the end integer radius and the start integer radius should not be less than 10.
- The step value should be greater than 0 and not greater than the difference between the end integer radius and the start integer radius.

The computed area value should be printed rounded to the **nearest hundredth**.

(**Hint:** define a function to print the header of the table, a second function to get the area value for a given radius value, a third function to print the footer of the table)

An Example: Start Integer radius (**startRad**) = 1, End Integer radius (**endRad**) = 10, Step Value (**stepVal**) = 1

Radius	Area of Circle
1	3.14
2	12.57
3	28.29
...	
10	314.29

[illegible]